

FumeGuard

Welding Fume Extraction Unit



Overview

- High quality extraction arm
- Available in 230V and 110V

Standard Features

- Disposable filter with high dust collection capacity
- Filter full indicator
- ON/OFF switch with motor protection
- Washable aluminium mesh spark arrestor

Applications

- Welding fume extraction
- All kinds of metal welding including high alloy steels
- Convenient for occasional usage

Main Filter

Filter Stages	2
Pre Filter Alu Mesh	G2 Class (Washable)
Main Filter	F9 Class
Total Filtration Area	
Main Filter	13m ²
Filtration Efficiency	
Standard	F9 Class
Optional	H13 Class
Optional Filters	
Pre Filter Pad	G4 Class
Pre Filter Cassette	M5 Class - 2m ²
Main Filter	H13 Class - 13m ²
Active Carbon Pad	Replaced w/ Pre Filter Pad
Active Carbon Cas	Replaced w/ Pre Filter Cassette

Basic Information

Extraction Capacity	1.000m ³ /h
Fan Capacity	1.950m ³ /h
Dimension (mm)	700 x 630 x 900mm
Weight (w/o Arm)	65kg
Motor Power	0,75kW
Power Supply	
Standard	230 V - 50Hz
Optional	110 V - 50Hz
Noise Level	75dB(a)

Additional Information

CE Certification	CE Certified
Fan Type	Radial Fan
No of Arms	1 pc
Arm Type	Filter Type
Arm Diameter	Ø160mm
Arm Length	2mt 3mt
Inlet Dimension	Ø50mm
HS Code	8421.39.85.90.00

Available in the UK exclusively through:

[Filtermist Limited](#)

Telford 54 Business Park, Nedge Hill, Telford, TF3 3AL

Tel +44 (0)1952 290500 Email sales@filtermist.com



www.filtermist.co.uk

Part of Absolent
Air Care Group